



DRY CEMENT & BARYTES HARDWALL

Heavy duty high performance suction and discharge hose for the bulk transfer of dry cement and barites from supply vessels to off-shore platforms and drilling rigs

Performance + Specs

Construction Tube

- Chemituf (Static Dissipating)

Cover

- SBR (Wrapped Finish)

Reinforcement

- Spiral-Plied Fabric
- Double Helix Wire

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Packaging

- Coiled & Poly-Wrapped

Branding

- CONTINENTAL DRY CEMENT HARDWALL ##### MADE IN CANADA
- CONTINENTAL BARYTES ##### MADE IN CANADA

DRY CEMENT HARDWALL

Order Codes: 549-275 (150 PSI Working Pressure), 549-617 (300 PSI Working Pressure)

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	4.84	121.00	100	Black	24	610	29	737	150	1.03	3.45	5.13	20263623
				200	Black	24	610	29	737	300	2.07	3.45	5.13	21025251
				400	Black	24	610	29	737	150	1.03	3.45	5.13	20263629
5	127.00	5.96	151.30	200	Black	30	762	29	737	150	1.03	5.63	8.382	20703501
				200	Black	30	762	29	737	300	2.07	5.63	8.382	20106491
				400	Black	30	762	29	737	150	1.03	5.63	8.382	20263640
				400	Black	30	762	29	737	300	2.07	5.63	8.382	20457606
6	152.40	6.98	177.20	100	Black	36	914	29	737	150	1.03	6.92	10.303	20147700
				200	Black	36	914	29	737	150	1.03	6.92	10.303	20266772

BARYTES HARDWALL

Order Codes: 549-070

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	4.77	121.00	100	Black	20	508	29	737	150	1.03	3.16	4.703	20169217
5	127.00	5.94	151.00	200	Black	25	635	29	737	150	1.03	5.41	8.051	20187158

